



HORIZONTAL AND VERTICAL REINFORCEMENT  
AS PER CODE OR AS SPECIFIED

CONCRETE SLAB REINFORCEMENT  
AS PER CODE OR AS SPECIFIED

SHORTER SCREW WITH SINGLE  
WASHER

LONGER SCREW WITH  
DOUBLE WASHER

24" [610mm]

AMDECK ECO 8"

ENDS OF 2x6" (38X140mm) DIMENSIONAL LUMBER  
JOISTS WRAPPED IN WATERPROOFING MEMBRANE  
BEFORE CONCRETE PLACEMENT

4" [102mm] MIN. BEARING

8" (203mm) R22 AMVIC ICF

1/2" (13mm) GYPSUM BOARD

# 8" AMDECK ECO TO ICF WALL LONGITUDINAL SECTION



1(877) 470-9991 [alleguard.com](http://alleguard.com)

22 November 2023

ALL DETAILS SHALL BE CONSTRUCTED IN ACCORDANCE WITH LOCAL BUILDING CODE AND CLIMATIC ZONE REQUIREMENTS. THE FOLLOWING INFORMATION IS PROVIDED AS A GUIDELINE ONLY AND CAN BE CHANGED WITHOUT NOTICE BY ALLEGUARD.